



GENERAL NOTE

1. THESE DRAWINGS ARE SCHEMATIC IN NATURE, AND NOT INTENDED TO SHOW ALL POSSIBLE CONDITIONS, MATERIALS, MANUFACTURING METHODS, OR EQUIPMENT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE SELECTION OF THE APPROPRIATE MATERIALS, MANUFACTURING METHODS, AND EQUIPMENT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE SELECTION OF THE APPROPRIATE MATERIALS, MANUFACTURING METHODS, AND EQUIPMENT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE SELECTION OF THE APPROPRIATE MATERIALS, MANUFACTURING METHODS, AND EQUIPMENT.
2. COORDINATE ALL WORK WITH ARCHITECTURAL, STRUCTURAL, MECHANICAL, AND ELECTRICAL TRADES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE SELECTION OF THE APPROPRIATE MATERIALS, MANUFACTURING METHODS, AND EQUIPMENT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE SELECTION OF THE APPROPRIATE MATERIALS, MANUFACTURING METHODS, AND EQUIPMENT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE SELECTION OF THE APPROPRIATE MATERIALS, MANUFACTURING METHODS, AND EQUIPMENT.
3. COORDINATE ALL WORK WITH ARCHITECTURAL, STRUCTURAL, MECHANICAL, AND ELECTRICAL TRADES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE SELECTION OF THE APPROPRIATE MATERIALS, MANUFACTURING METHODS, AND EQUIPMENT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE SELECTION OF THE APPROPRIATE MATERIALS, MANUFACTURING METHODS, AND EQUIPMENT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE SELECTION OF THE APPROPRIATE MATERIALS, MANUFACTURING METHODS, AND EQUIPMENT.
4. ALL DRAINAGE PIPING SHALL BE CONCEALED BEHIND WALLS AND PRE CHASES OR ABOVE CEILINGS, HOLD DRAINS AND GAS SERVICES AT APPROXIMATELY 9'-0" FROM BUILDING STRUCTURE, UNLESS NOTED OTHERWISE.
5. CONTRACTOR SHALL MAKE FINAL CONNECTION TO ALL DOMESTIC WATER, SANITARY SEWERS, STORM DRAINS AND GAS SERVICES AT APPROXIMATELY 9'-0" FROM BUILDING STRUCTURE, UNLESS NOTED OTHERWISE.
6. DRAIN WATER HEATERS, PUMPS AND TANKS TO FLOOR SLABS OR CONCRETE PADS.
7. COORDINATE UNDERGROUND PIPING WITH GRADE BEAMS AND WALL FOOTINGS.
8. REFER TO ARCHITECTURAL PLANS AND ELEVATIONS FOR LOCATION ALL PLUMBING FIXTURES. EXACT LOCATION OF ALL PLUMBING FIXTURES MUST BE VERIFIED IN FIELD PRIOR TO INSTALLATION. FINAL LOCATION SHALL BE AS DIRECTED BY ARCHITECT.
9. FLOOR DRAINAGE SHALL BE LOCATED ON ARCHITECTURAL DRAWINGS. DRAINAGE SHALL SLIDE TO FLOOR DRAINS, MAXIMUM SLOPE SHALL BE 1/4" PER FOOT. DRAINAGE SHALL BE LOCATED ON ARCHITECTURAL DRAWINGS. DRAINAGE SHALL SLIDE TO FLOOR DRAINS, MAXIMUM SLOPE SHALL BE 1/4" PER FOOT. DRAINAGE SHALL BE LOCATED ON ARCHITECTURAL DRAWINGS. DRAINAGE SHALL SLIDE TO FLOOR DRAINS, MAXIMUM SLOPE SHALL BE 1/4" PER FOOT.
10. PLUMBING CONTRACTOR SHALL MAKE FINAL CONNECTIONS TO ALL EQUIPMENT LOCATED ON DRAWINGS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE SELECTION OF THE APPROPRIATE MATERIALS, MANUFACTURING METHODS, AND EQUIPMENT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE SELECTION OF THE APPROPRIATE MATERIALS, MANUFACTURING METHODS, AND EQUIPMENT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE SELECTION OF THE APPROPRIATE MATERIALS, MANUFACTURING METHODS, AND EQUIPMENT.
11. DO NOT RUN PLUMBING PIPING OR PRE PROTECTION PIPING THROUGH TRANSFORMER WALLS, ELECTRICAL CLOSETS OR ELECTRICAL SWITCHGEAR ROOMS.
12. PROVIDE BASE CLEAVANT AT LOWEST FLOOR LEVEL OF ALL SANITARY SEWER AND DRAINAGE PIPES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE SELECTION OF THE APPROPRIATE MATERIALS, MANUFACTURING METHODS, AND EQUIPMENT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE SELECTION OF THE APPROPRIATE MATERIALS, MANUFACTURING METHODS, AND EQUIPMENT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE SELECTION OF THE APPROPRIATE MATERIALS, MANUFACTURING METHODS, AND EQUIPMENT.
13. ALL STRUCTURAL PENETRATIONS (SLEEVES, BLOCKS, ETC.) TO BE LOCATED AND COORDINATED IN THE FIELD BY THE CONTRACTOR IN RELATION TO THE REQUIREMENTS OF FINAL EQUIPMENT AND FINISHES SELECTED.
14. PROVIDE ALL NECESSARY WATER HEATERS, PUMPS, ETC., OR EQUIPMENT OF EQUIPMENT.

① SEE DETAIL 2/42-P10 FOR PIPING

NOTES:

- ① DELETED
- ② DELETED
- ③ DELETED
- ④ DELETED
- ⑤ REFER TO DETAIL 1/42-P10



Office of Facilities

 Department of Veterans Affairs

